

DARKID

Blockchain based anonymous distributed ID system

Proof of Concept

19th January 2018



arnaucode.com



[@arnaucode](https://twitter.com/arnaucode)

MAIN CONCEPT

- Guarantee a decentralized login system
- Make sure that register users are real ones
 - Guarantee that there are no bots generating large amounts of fake accounts
- Ensure that only verified users can generate anonymous IDs (darkID)

MOTIVATION

- Traditional Login Systems are owned by few big corporations
 - “Information is power. But like all power, there are those who want to keep it for Themselves.”
- Aaron Swartz
- With centralized systems the power to censor, ban, delete users is in few hands
- We need to build an internet with decentralized systems, to decentralize power

BASIC FUNCTIONALITIES

- Verify the identity of an user
 - Based on the
 - Username, Email, Phone, ID card, ...
- Generate anonymous ID (darkID) and get that ID signed by a serverSigner with high reputation
- Inject the darkID into the ethereum blockchain using a Smart Contract
- Authenticate in the platforms using the darkID, that is public in the ethereum blockchain

ELEVATOR PITCH

- This is Marie
- Marie wants to surf the net, without being identified
- But also, Marie don't want a net full of bots and fake accounts
- Marie wants a login system based on cryptography, to ensure anonymity
- Also wants to ensure that only verified users can use the login system
- Marie loves decentralized systems
- Marie loves ethereum smart contracts
- Marie loves darkID



TECHNOLOGIES USED

- Desktop App
 - Angularjs + Electron + Go lang
- Backend
 - Go lang
 - Solidity (Ethereum)



FIRST PROTOTYPE - 'BLOCKCHAINIDSYSTEM'


Everything from scratch:

- Written own RSA library
- Written own peer-to-peer network
- Written own blockchain algorithms over the p2p network
- Written Server-ID-Signer
- Written Desktop App

<https://github.com/arnaucode/blockchainIDsystem>

Project not finished and currently abandoned

FIRST PROTOTYPE



- peers
 - the peers of the p2p network that runs the blockchain
- serverCA
 - Is a REST server that has been certified (is the Certified Authority) to validate the peers that will be able to participate of the blockchain.
 - Have the webapp (frontend) to validate peers through a GUI interface
 - The GUI frontend webapp allows also to view the current peers of the network and the blocks of the blockchain
- server-ID-signer
 - The server where the user creates a non anonymous account
 - Also is the server that blind signs the Anonymous ID of the users
 - Have the webapp (frontend) to interact through a GUI interface
 -

FIRST PROTOTYPE

Problems:

- Implement a production ready peer-to-peer network is not so easy
 - Gnutella, distributed hash tables, freenet, ...
- Use own cryptographic algorithms for real world solutions is not a good idea
- Implement a blockchain system needs to add some of Proof-of-Work, Proof-of-Stake, Proof-of-Cooperation, ... system → too much code for a small university subject project

FIRST PROTOTYPE - 'BLOCKCHAINIDSYSTEM'

First Prototype short demo

```
clientApp/  
documentation/  
.git/  
.gitignore  
LICENSE  
peer/  
README.md  
runTmuxTestPeers.sh  
serverCA/  
serverIDsigner/  
tests/  
tmuxTest.sh  
xtermRunTestPeers.sh
```

- At some point, I realized that this is not the way
- Better use ethereum smart contracts instead of developing own p2p network and own blockchain (assuming small amount of time for developing this university subject project)

2ND PROTOTYPE:



Blockchain based anonymous distributed ID system


<https://github.com/arnaucode/darkID>

2ND PROTOTYPE: DARKID

- Instead of developing own p2p network and own blockchain → use ethereum blockchain and ethereum Smart Contracts
- Use of Go existing cryptographic algorithms
- Written Server-ID-Signer
- Written Desktop App




DARKID



- server-ID-signer
 - The server where the user creates a non anonymous account
 - Also is the server that blind signs the Anonymous ID of the users
 - Have the webapp (frontend) to interact through a GUI interface
- Desktop App
 - Asdf
- ethereum Smart Contracts
 - Where the darkIDs are stored

DESKTOP APP



DESKTOP APP

The screenshot shows a desktop application window titled "darkID". The browser address bar displays "http://127.0.0.1:3130/" and the user is logged in as "user01@dark.id". The main content area is titled "My IDs" and contains a "CREATE NEW ID" button. Below this, there are three entries, each with a unique ID string, status tags, a timestamp, and action buttons.

ID	Status	Timestamp	Action
CJkpQmm7H9Zq4JLDrraexpPcmc9XI6oZy6iM7AyTL	Verified, Signed, In Blockchain	29.12.2017, 20:28:35h	USE ID, Delete
tKnX0SY2tAVQGsmkvTtkIitw8tFY9h_G1b4ZDQchA	Verified, Signed	29.12.2017, 20:28:36h	ADD TO BLOCKCHAIN, Delete
75ZIZeAeGmb2xPM91hZas2J4va06yMrCdgybJR4WC	Not verified, Not signed	29.12.2017, 20:28:40h	SEND TO SERVERIDSIGNER, Delete

DESKTOP APP



HOW DARKID WORKS? STEP BY STEP PROCESS

1. The user registers a non anonymous user (using email, phone, password, etc), and performs the login with that user
2. The user, locally, generates a RSA key pair (private key & public key)
3. The user blinds his Public-Key with the server-ID-signer Public-Key
4. The user's Public-Key blinded, is sent to the server-ID-signer
5. The server-ID-signer Blind Signs the Public-Key blinded from the user, and returns it to the user
6. The user unblinds the Public-Key signed by the server-ID-signer, and now has the Public-Key Blind Signed by the server-ID-signer

HOW DARKID WORKS? STEP BY STEP PROCESS

7. The user sends the Public-Key blind signed to the p2p network
8. The peers verify that the Public-Key Blind Signed is correctly signed by the server-ID-signer, if it is, they add the Public-Key to the Ethereum Blockchain, inside a new block
9. Then, when the user wants to login into a platform, just needs to put his Public-Key
10. The platform goes to the Ethereum Blockchain, to check if this Public-Key is registered in the blockchain
11. The platform sends a message encrypted with the user Public-Key, and the user returns the message decrypted with the Private-Key, to verify that is the owner of that Public-Key

RSA AND BLIND SIGNATURE

RSA encryption system

https://en.wikipedia.org/wiki/RSA_cryptosystem

- Public parameters: (e, n)
- Private parameters: (d, p, q, ϕ, σ)
- Public-Key = (e, n)
- Private-Key = (d, n)
- Encryption: $c \equiv m^e \pmod{n}$
- Decryption: $c^d \equiv (m^e)^d \equiv m \pmod{n}$

Blind signature process

https://en.wikipedia.org/wiki/Blind_signature

- m is the message (in our case, is the Public-Key of the user to be blinded) $m' \equiv mr^e \pmod{N}$
- server-ID-signer blind signs m' $s' \equiv (m')^d \pmod{N}$.
- user can unblind m , to get m signed $s \equiv s' \cdot r^{-1} \pmod{N}$
- This works because RSA keys satisfy this equation $r^{ed} \equiv r \pmod{N}$
- and this $s \equiv s' \cdot r^{-1} \equiv (m')^d r^{-1} \equiv m^d r^{ed} r^{-1} \equiv m^d r r^{-1} \equiv m^d \pmod{N}$.

DARKID GENERATION




ethereum
network



user



server-ID-signer



DARKID LOGIN



DARKID

DEMO TIME

```
clientApp  
darkID-library-login-example  
documentation  
eth  
LICENSE  
README.md  
runTmuxDeploy.sh  
serverIDsigner
```

CONCLUSIONS

- It was funny starting to implement a p2p network and a blockchain from scratch
- But makes no sense having not so much time in a short university subject
- ethereum smart contracts have a lot of potential uses
- Current version is far from a stable release for real use
- Can be an option for a Final Degree Project:
 - Develop an entire blockchain from scratch, with some alternative to PoW and PoS
- darkID have lots of applications
 - For social networks, anonymous voting systems, leaks system, ...
 - Better use over Tor network